


NEW **NEEDLE**

The slender shape of the Needle family brings a touch of elegance into any project. Slim tubes, just carelessly hanging down from the ceiling or cleverly peeking around to throw a highlight wherever needed. Combine multiple fixtures to create playful clusters or use it as a single luminaire in all its simplicity.

www.deltalight.com/needle

DESIGN BY NITEO LIGHTING FOR DELTA LIGHT®



**CONNECTION
TRIMLESS O.F.A.**


- 62 x 80 9 or 12
- 102 x 80 (CONCRETE)

328 10 03

4A / 250V

0,2


NEEDLE 1 TRC



3000K / CRI>90		2700K / CRI>90	
LED [E] 4,1W / 380lm / 350mA LED [E] 6W / 515lm / 500mA LED [E] 8,3W / 673lm / 700mA		LED [E] 4,1W / 355lm / 350mA LED [E] 6W / 481lm / 500mA LED [E] 8,3W / 629lm / 700mA	
13°	33°	13°	33°
25014 9310 ◊	25014 9320 ◊	25014 9210 ◊	25014 9220 ◊
◊ BBR / FG			
◊ 0,2 IP20			

REQUIREMENTS
LED POWER SUPPLY 350-500-700mA-DC / DIM
CONNECTION TRIMLESS O.F.A.


NEEDLE 1 OK TRC



3000K / CRI>90		2700K / CRI>90	
LED [E] 4,1W / 380lm / 350mA LED [E] 6W / 515lm / 500mA		LED [E] 4,1W / 355lm / 350mA LED [E] 6W / 481lm / 500mA	
13°	33°	13°	33°
25015 9310 ◊	25015 9320 ◊	25015 9210 ◊	25015 9220 ◊
◊ BBR / FG			
◊ 0,2 IP20			

REQUIREMENTS
LED POWER SUPPLY 350-500mA-DC / DIM
CONNECTION TRIMLESS O.F.A.


NEEDLE 1



3000K / CRI>90		2700K / CRI>90	
LED [E] 4,1W / 380lm / 350mA LED [E] 6W / 515lm / 500mA LED [E] 8,3W / 673lm / 700mA		LED [E] 4,1W / 355lm / 350mA LED [E] 6W / 481lm / 500mA LED [E] 8,3W / 629lm / 700mA	
13°	33°	13°	33°
25010 9310 ◊	25010 9320 ◊	25010 9210 ◊	25010 9220 ◊
◊ BBR / FG			
◊ 0,3 IP20			

REQUIREMENTS
LED POWER SUPPLY 350-500-700mA-DC / DIM


NEEDLE 2



3000K / CRI>90		2700K / CRI>90	
2 x LED [E] 4,1W / 380lm / 350mA 2 x LED [E] 6W / 515lm / 500mA 2 x LED [E] 8,3W / 673lm / 700mA		2 x LED [E] 4,1W / 355lm / 350mA 2 x LED [E] 6W / 481lm / 500mA 2 x LED [E] 8,3W / 629lm / 700mA	
13°	33°	13°	33°
25012 9310 ◊	25012 9320 ◊	25012 9210 ◊	25012 9220 ◊
◊ BBR / FG			
◊ 0,6 IP20			

REQUIREMENTS
LED POWER SUPPLY 350-500-700mA-DC / DIM


NEEDLE 1 OK



3000K / CRI>90		2700K / CRI>90	
LED [E] 4,1W / 380lm / 350mA LED [E] 6W / 515lm / 500mA		LED [E] 4,1W / 355lm / 350mA LED [E] 6W / 481lm / 500mA	
13°	33°	13°	33°
25011 9310 ◊	25011 9320 ◊	25011 9210 ◊	25011 9220 ◊
◊ BBR / FG			
◊ 0,3 IP20			

REQUIREMENTS
LED POWER SUPPLY 350-500mA-DC / DIM

NEEDLE 2 OK



3000K / CRI>90		2700K / CRI>90	
2 x LED [E] 4,1W / 380lm / 350mA 2 x LED [E] 6W / 515lm / 500mA		2 x LED [E] 4,1W / 355lm / 350mA 2 x LED [E] 6W / 481lm / 500mA	
13°	33°	13°	33°
25013 9310 ◊	25013 9320 ◊	25013 9210 ◊	25013 9220 ◊
◊ BBR / FG			
◊ 0,6 IP20			

REQUIREMENTS
LED POWER SUPPLY 350-500mA-DC / DIM



INTERIOR DESIGN: BURO HC

